














Climatic Chambers

Climatic chambers with ultrasonic humidifier

										
Parameter										
Price	€ 8.000	€ 9.785	€ 10.825	€ 12.890	€ 11.960	€ 13.195	€ 13.920	€ 15.430	€ 16.185	
air convection	forced									
chamber capacity [l]	109	240	322	416	470	600	749	1330	1485	
working capacity [l]	109	240	283	416	392	485	749	1132	1264	
door type	double (external solid, internal glass) / external glass (option)									
temperature range [°C]	-				-10...+60					
FIT version					-10...+60 (with light on +10...+50)					
temperature resolution [°C]					every 0,1					
relative humidity range [%]	30...90 (see working temperature and humidity chart for details on page 62)									
humidity resolution [%]	every 1									
controller	microprocessor with external LCD graphic display									
interior	acid-proof stainless steel to DIN 1.4301									
housing	INOX/G			stainless steel linen finish						
nominal power [W]	1350	1550	1850	2250	1850	2850	3450	3450		
weight [kg]	90	140	125	185	130	170	275	220	230	
power supply*	230 V 50 Hz									
shelves fitted/max	2/7	3/10	3/11	3/14	3/11	3/11	5/16	2x3/11	2x3/11	
warranty	24 months									
all the above technical data refer to standard units (without optional accessories)										

Climatic chambers with steam humidifier

				
Parameter				
Price	€ 8.000	€ 9.785	€ 12.890	€ 13.920
air convection	forced			
chamber capacity [l]	109	240	416	749
working capacity [l]	109	240	416	749
door type	double (external solid, internal glass) / external glass (option)			
temperature range [°C]	-10...+100			
temperature resolution [°C]	every 0,1			
relative humidity range [%]	0 (see working temperature and humidity chart for details on page 62)			
humidity resolution [%]	every 1			
controller	microprocessor with external LCD graphic display			
interior	acid-proof stainless steel to DIN 1.4301			
housing	INOX/G stainless steel linen finish			
nominal power [W]	2850	3050	3700	4350
weight [kg]	103	140	185	275
over temperature protection	class 3.3 to DIN 12880			
power supply*	400 3/N			
shelves fitted/max	2-jul	3-okt	mrt-14	mei-16
warranty	24 months			